


LINED HOLD DOWN U-STRAP DIMENSIONS										
PIPE SIZE (nps)	METALLIC STRAP DIMENSIONS (in.)						LINER DIMENSIONS (in.)		CENTER OF PIPE TO BOS* (in.)	
	A	B	C	D	E	F	G	H	I	
0.75	29/16	111/16	1/4	2	3/8	2 1/2	1/4	2	1/4	
1	2 15/16	2	1/4	2	3/8	2 3/4	1/4	2	3/8	
1.5	37/16	29/16	1/4	2	3/8	2 5/6	1/4	2	1/2	
2	37/8	3	1/4	2	3/8	3	1/4	2	3/4	
3	51/8	4 1/8	1/4	2	1/2	3 1/2	1/4	2	1	
4	61/8	5 1/8	1/4	2	1/2	4	1/4	2	1 1/2	
6	83/8	7 1/4	1/4	2	5/8	7	1/4	2	2	
8	103/8	9 1/4	1/4	2	5/8	7	1/4	2		
10	127/8	11 3/8	3/8	2 1/2	3/4	8	1/4	2 1/2		
12	15	133/8	3/8	2 1/2	7/8	9 3/8	1/4	2 1/2	2 1/2	
14	16 1/4	14 5/8	3/8	2 1/2	7/8	10 5/8	1/4	2 1/2		
16	18 1/2	16 5/8	1/2	3	7/8	11 1/2	1/4	3		
18	20 5/8	18 5/8	1/2	3	1	13	1/4	3		
20	22 5/8	20 5/8	1/2	3	1	14	1/4	3		
24	26 5/8	24 5/8	1/2	3	1	16	1/4	3		

\* BOS- Bottom of Strap

NOTES:

1. Hold down strap to be hot-dipped galvanized (other finishes available upon request).
2. Liner to be APP-UT80A Urethane (Urethane properties can be modified if necessary for hardness parameters).
3. Custom dimensions available upon request.
4. Temperature Range: -40° F to +175° F.

ITEM	QTY	DESCRIPTION	Material
1	1	Hold Down Strap	HDG CS
2	4	Nuts	HDG CS
3	2	Washers	HDG CS
4	1	Liner	APP-UT80A Urethane

CUSTOMER	DWN.	DATE	05-29-2015		 <p>5611 Guhn Road, Suite A1 Houston, Texas 77040 1-888-408-9872 • WWW.APPMFG.COM</p>	
DATE	CHK.					
CD, NAME	ENG.					
CDNTACT1	APPR.					
N- PRDGEN	MFG. App	s	<input checked="" type="checkbox"/>			
N- CLIENT				DWG DESCRIPTION		
CLIENT				Urethane-lined Hold Down Strap		
PRDJCT-				SIZE A	ULHDS0515	REV. Q
REF.	NEXT ASSY	QTY	SCALE	NONE	EST. WT.	SHEET 1 OF 1